



DATA DISPLAY RS 485

- 4-DIGIT PROGRAMMABLE PROJECTION
- INPUT: RS 485
- ASCII, MODBUS-RTU
- SIZE OF DIN 50,5 X 28,5 MM
- POWER SUPPLY 10...30 VDC/24 VAC

OMM 335RS



OMM 335RS is a 4-digit data display from the serial line RS 485.

The instrument is based on a microcontroller and an A/D converter, which ensures good accuracy and easy operation of the instrument.

The 22 mm cross-section of the circular instrument body allows its convenient mounting into mosaic and signaling panels.

OMM 335RS

DATA DISPLAY RS 485

OPERATION

The instrument is set and controlled by two buttons located on its the body.

Standard equipment is the OM Link USB interface, which, when using the control program, allows you to edit and archive all device settings and to update firmware.

All settings are stored in FLASH memory (they hold even after the power is turned off).

STANDARD FUNCTIONS

PROGRAMMABLE PROJECTION

Input: RS 485

Protocol: ASCII - Master/Slave/Universal or MODBUS RTU

Projection: 9999

NEW

TECHNICAL DATA

INPUT

RS	Input	RS 485
	Protocol	<p>ASCII - Master</p> <ul style="list-style-type: none"> - the instrument controls data sending from the slave system - „COMM“ can be used to select the received data - the instrument asks with the rate of 10 queries/s <p>ASCII - Slave</p> <ul style="list-style-type: none"> - Passive bus display where other devices or computers communicate in „MAST.“ mode. If the „COMM“ and the requested data are correctly received, they will be displayed by the instrument <p>ASCII - Universal</p> <ul style="list-style-type: none"> - in dynamic menu items (Stat, Ad.Un, Sign, Data, Stop, Req.) you can build your own communication protocol format
	MODBUS RTU	
	Format	8 bit + no parity + 1 stop bit
	Rate	300...230 400 Baud
	Line termination	short-circuit jumper on the connector

PROJECTION

Display: -999...9999, single color 7-segment LED
Digit height: 14 mm
Display color: red or green
Decimal point: adjustable - in menu
Brightness: adjustable

INSTRUMENT ACCURACY

TK: 50 ppm/°C
OM Link: Company communication interface for operation, setting and update of instruments.
Watch-dog: reset after 500 ms
Calibration: at 25°C and 40 % r.h.

POWER SUPPLY

Range: 24 V DC/AC, ±10 %, PF≥0.4, I_{STP}< 45 A/11 ms
 10...30 VDC/24 VAC, ±10 %, PF≥0.4, I_{STP}< 45 A/11 ms, isolated
Consumption: < 0,2 W/0,2 VA

MECHANIC PROPERTIES


Material: PA66, incandubstible UL 94 V-1
Dimensions: 50,5 x 28,5 x 66 mm [w x h x d]
Panel cutout: ø 22,5 mm

OPERATING CONDITIONS

Connection: connector terminal blocks, section < 1,3 mm²
Stabilization period: within 15 minutes after switch-on
Working temperature: -20°...60°C
Storage temperature: -20°...85°C
Protection: IP65 (front panel only)
El. safety: EN 61010-1, A2
Dielectric strength: 700 VAC per 1 min test between supply and input
Insulation resistance: for pollution degree II, measuring cat. II, power supply > 250 V [PI]
EMC: EN 61326-1

PI - Primary insulation, DI - Double insulation

CONNECTION



ORDER CODE

OMM 335RS

- [] - []

Power supply	10...30 V AC/DC	0	
	24 V AC/DC	2	
Display color	red	1	
	green	2	
Specification	customized version, do not fill in		00

Basic configuration of the instrument is indicated in bold.